



Technical specification

Length overall	30.1 m
Beam overall	7.05 m
Draft approximate	1.6 m
Guest accommodation	6 people
Crew accommodation	6 people
Hull material	Cold Molding Yacht Construction with thickness 40 mm
Glass of windows	Tempered triplex surface (8*8) mm
Stainless steel	AISI Grades (300 Series) 316
Accommodation	1 Mater Room – 2 Guest Room – 3 Crew Room
Main saloon	2 Custom sofa – 2 Armchair – 2 pouf – 1 TV unit 1 – 1 Table
Second Saloon	2 Custom sofa – 1 TV unit – 1 Table
Sun deck	2 Custom sofa – 1 Dining table – 1 zodiac
Exterior teak	Artificial teak decks
Fresh Water	4000 L / Water Maker MC4 Duplex Version (2*210 LPH)
Diesel Fuel	10800 L
Waste Gray Water	1000 L
Slop Lubricants	300 L

Sanitary waste	1000 L
Weight estimate	110 T
Maximum Speed	20 knots
Cruise Speed	16 knots
Cruise Range	400 miles
power	Twin MTU/DDC marine diesels model 12V2000M96 1800 bhp each total 3600 hp Specific fuel consumption 215 g/kWh 2 Nanni generator 45 KVA 1 Nanni night generator 13 KVA
Naval architect	Timucin Yildiran (Turkey)
Interior designer	StudioVafiadis (Italy)
Air condition	Chiller system (CLIMMA)
Oil water separators	Alfa Laval MIB 503 Separator
Sewage treatment	Ecomar 20 SX pp
Toilet	Vacuum system (TECMA)
Hydraulic system	DZC 1400-2 HPI / Kr-14L ANCHOR WINDLASS DHC 1600 HPI / Kr CAPSTAN DDS 2x550 HYDRAULIC STEERING GEAR Hydraulic Thruster models SH420,SH550
Crane	TELESCOPIC FLYBRIDGE CRANE 3010 ((Opecmare)
Gangway	STAINLESS STEEL BOX GANGWAY 1003((Opecmare)
stabilizer	FIN AND INTERCEPTOR (HUMPHREEE)
Doors	Telescopic Automatic doors (Tempesta) Garage door (Opecmare) Watertight door for engine room (Opecmare)
Navigation equipment	GA 38 GPS GLONASS Antenna Garmin GPS 19x NMEA 2000 Antenna Garmin GPSMAP 8416 XSV 1 with sonar function GMR™ 424 xHD2 Open Array Radar and Pedestal